

# AF-25K II



**5-25kg**  
Weighing Range

**±10g**  
Accuracy

**1600+Pcs/h**  
Speed



Stable  
Performance



Easy  
Installation



Servo Motor  
Control



Weighing  
Accuracy

## Features

- **Granular Materials:** Designed for plastic particles, granular fertilizers, feed, and other similar materials.
- **Easy Dismounting:** Modular design of the measuring hopper allows for easy cleaning.
- **Parameter Setting:** Features a self-adjust function with customizable target value settings.
- **Stable Performance:** The feeding process is precisely controlled by a servo motor for reliable operation.
- **Weighing Accuracy:** Supports a weighing range of 5-25kg, with a speed of up to 900 pieces per hour and a best accuracy of ±25g.



## Optional:



Bag Clamp

SS304 Stainless Steel



10-inch touch screen

User-friendly interface design,  
vivid display, and easy to operate



# AF-25K II

Specification	
Model	AF-25K II
Weighing Range	5 ~ 25kg
Division	1g
Best Accuracy	±10g
Speed	≤1600 pcs/h
Volume	55Lx2
Feeding Method	Feeding control by servo, pneumatic discharging
Material	SS304, Carbon Steel
I/O	8 Output (5v), 8 Input (24V)
Communication	RS485, Modbus TCP/IP
Pneumatic	0.4 ~ 0.6 MPa
Power	Single Phase AC-220V±10%, 50/60HZ
Working Environment	0 ~ 40°C, 90% R.H Condensation Is Not Allowed

\*Normally, the diameter of the testing material 1-5mm

## Structure and Dimensions

Unit: mm

