

AT-30T



The bulk weighing scale divides a batch of bulk materials into several parts, weighing and accumulating each batch to obtain the total weight of bulk materials. It is suitable for weighing various granular materials and meets trade regulation.

5-30 t/h

Flow rate range

30 t/h

Maximum flow rate

55 L

Hopper volume



Stable
Performance



Easy
Installation



Servo Motor
Control



Weighing
Accurate

Features

- **Intelligent speed adjustment:** only need to set the target value, the scale will automatically adjust the optimal quantitative speed while ensuring accuracy.
- **Simple installation:** standard flange interface, fast installation.
- **Easy data export:** USB for export data records.
- **Convenient operation:** 7-inch/10-inch touch screen optional.
- **Safe materials:** 304 stainless steel for the part in contact with the material.
- **High speed and high precision:** free-fall feeding is fast and accurate.

Optional:



10-inch touch screen

User-friendly interface design, vivid display, and easy to operate.



NONIS
Impianti di pesatura industriali



info@nonisbilance.com
www.nonisbilance.com

P.zza Elvo Tempia 12, Cossato (BI)
+39 0159842291

AT-30T

Specification	
Model	AT-30T
Power	AC220V \pm 10%, 50/60 HZ, 1000W
Flow rate range	5 ~ 30 t/h
Maximum speed	30 t/h
Hopper volume	55L
Working temperature	0 ~ 40°C
Maximum humidity	90% R.H No condensation
Air source	0.4 ~ 0.6 MPa 2m ³ /h

*Normally, the diameter of the testing material 1-5mm

Structure and Dimensions

Unit : mm

